



## About the Solution

The **SCR25** also acts as a USB hub and Video over **USB3.0** gives you excellent connectivity to share your ideas with colleagues and business partners alike. The **SCR-25** also uses Bluetooth® wireless technology to provide a cable-free solution for users who prefer conferencing via mobile phone

The **HuddleCam 3X** will give your video conference clear and wide coverage of all participants and the **DTM-1 microphone** will ensure everyone is heard equally around the room.

You can also look forward to interact with your presentation by using the touch screen to make notes and share ideas live.

## Cabling Key

-  HDMI
-  Rj45 CABLE
-  USB EXTENDER
-  USB 3
-  BLUETOOTH

## Equipment list

### Devio SCR25

- Works in concert with PCs running web-based conferencing solutions, including Microsoft Skype for Business/Microsoft Teams, Zoom, BlueJeans, Google Hangouts™/Google Meet, and many more.
- Supports both Windows and Mac PCs, and uses standard audio drivers
- Supports driverless, pass-through HDMI connectivity to a single in-room display, or to two monitors with USB video using DisplayLink1 USB graphics technology
- Auto Setup validates device connections, adjusts room levels, and sets speaker EQ to optimize audio quality
- Supports Bluetooth wireless technology Can be monitored and managed remotely via SNMP or with the Devio System Administration Utility (SAU)
- Firmware updates can be scheduled and deployed to multiple Devio units via the SAU
- Speaker connectivity options include HDMI audio, a built-in 20W amplifier, or RCA line out
- Ships with a mounting bracket for under-the-table installation, and one DTM-1 tabletop or one DCM-1 ceiling microphone

### Huddlecam HC3X-BR-G2

- Plug-and-play USB interface, PC and Mac compatibility
- Up to 1080p30 uncompressed video via USB 3.0 (requires quad-core processor) or 720p30 via USB 2.0
- 82° field of view suitable for medium to large conference rooms
- Compatible with most VC software programs
- Illuminated blue/orange LED lights for in-use/standby modes
- Auto/manual/outdoor/indoor/one-push/ATW white-balance options for aligning color-temperature
- Choose up to 64 preset movements with the included IR remote control
- RS-232 input/output can be converted to USB for computer-based control