

MODEL



Zero-Ohm Price List
DESCRIPTION



RETAIL
EXCL VAT

01 October 2019

ZERO-OHM System is a passive device that interconnects between any amplifier and multiple loudspeakers without the concerns of amplifier speaker loads, impedance and extremely long cable runs. This Patented Design eliminates the need for 70V-100V transformer products. Multiple loudspeakers can be wired in a parallel connection to impedances below one (1) Ohm.

Applications: Shopping Malls, Hotels, Airports, Amusement Parks, Stadiums, Cinemas, Banquet Halls, Cruise Ships, Outdoor Malls, Hospitals, Restaurants, Warehouses, Universities, Water Parks, Bars, Car Audio and more

MS-4R

Features: Zero (0) Ohm functionality, No transformers required, Multiple loudspeakers can be connected in parallel, Any Speaker impedance can be used: 2/4/8/16 Ohm, Uniform power distribution over long distance cable runs, Full range frequency response, Identical Output Phase relationship with all Power Amplifiers.
Acoustic Performance: Frequency Response: 20Hz-20kHz. Frequency Range: 20Hz-20kHz. Audio: Input/Output Connector: Neutrik NL4 Input Pin-Out: Pin 2+, Pin 2- Output Pin-Out: Pin 1+, Pin 1- Minimum Output Impedance: 0.1Ohms Max. Power Handling: 4000W. Physical Properties: Height: 65.1mm Width: 438.1mm/479.4 with Rack Ears. Depth: 149.2mm. Weight: 3.2kg. Shipping weight: 4Kg.

31 000,00

